## NSN 5935-01-341-2296

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-341-2296 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/strain relief **Overall Length:** 2.381 inches **Overall Diameter:** 2.203 inches **Environmental Protection:** Corrosion resistant and vibration resistant and shock resistant **Cable Entrance Diameter:** 0.657 inches **Distance From Mounting Shoulder To Front Face:** 0.912 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.250 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-48 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Cable clamp **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.625 inches

Insert Material:

Plastic single mating end

## NSN 5935-01-341-2296

Electrical Receptacle Connector Body - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Bushing Accommodation Hole Shape:
Round
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0