Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-341-3188

Body Style:
Straight shape
Overall Length:
8.940 inches
Overall Height:
0.560 inches
Overall Width:
0.500 inches
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.145 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Features Provided:
Low insertion force contact
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate
Shell Surface Treatment Specification:
Mil-c-5541, cl 3 or 1a military specification single treatment response
Shell Material Specification:
Qq-a-250/11 federal specification single material response
Included Contact Quantity:
150 single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:

Hermaphrodite single mating end single contact grouping

Special Features:

Insulators black in positions 10, 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 120, 130 and 140; remaining insulators natural

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.150 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5541 spec.