Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-341-5668

## **Overall Length:**

0.315 inches

## **Distance From Mounting Shoulder To Front Face:**

Between 0.170 inches and 0.175 inches

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Nonstd single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## Connector Locking Method:

Friction

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Plastic methacrylate single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 0 military specification 1st treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

L-p-380 federal specification single material response single mating end

## **Included Contact Quantity:**

1 single mating end single contact grouping

#### Included Contact Type:

Coaxial pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surface gold

## **Precious Material And Weight:**

0.005 gold grains, troy

#### **Precious Material:**

Gold

## Shelf Life:

N/a

#### Unit Of Measure:

---



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.