NSN 5935-01-341-5676

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-341-5676

Body Style: Straight shape w/solder mount **Overall Length:** 1.067 inches **Overall Diameter:** Between 0.828 inches and 0.860 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 40495 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Bayonet pin **End Application:** 6610-01-164-8092 indicator, altimeter **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:** Tin **Included Contact Quantity:**

13 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

NSN 5935-01-341-5676

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.013 gold grains, troy
Precious Material:
Gold
Specification Data:
98810-203770 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.