

View Online at <https://aerobasegroup.com/nsn/5935-01-341-6794>

Thread Class:

2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

33.66 millimeters

Overall Height:

Between 25.9 millimeters and 26.5 millimeters

Overall Width:

Between 25.9 millimeters and 26.5 millimeters

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and shock resistant and oil resistant and thermal shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 18.26 millimeters and 20.62 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 18.26 millimeters and 20.62 millimeters

Distance From Mounting Shoulder To Front Face:

Between 19.5 millimeters and 20.9 millimeters

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

36100 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 105.0 and 140.0 and 204.0 and 307.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Thready Qty Per Inch (tpi):

10

Thread Size:

15.0 millimeters and 0.750 inches

Thread Pitch In Millimeters:

1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Thread Tolerance Class:

6g external

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Iso m and special acme

Specification Data:

81349-mil-c-38999/20 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.