

View Online at <https://aerobasegroup.com/nsn/5935-01-341-7337>

Thread Class:

2a

Thread Direction:

Right-hand and right-hand

Overall Length:

2.062 inches

Overall Height:

0.625 inches

Overall Width:

0.625 inches

Threaded Device Type:

Mounting bushing and mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Features Provided:

W/circuit protection device

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches and 3.0 millimeters

Thread Pitch In Millimeters:

0.50

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Thread Tolerance Class:

6h internal

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and iso s

Specification Data:

28480-1250-1824 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.