Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-342-0342

#### **Body Style:**

Straight shape

#### **Overall Length:**

3.500 inches

# **Overall Height:**

0.820 inches

#### **Overall Width:**

0.330 inches

**Body Length:** 

3.500 inches

#### **Environmental Protection:**

Pressure proof and humidity resistant and vibration resistant and shock resistant

#### Distance Between Mounting Facility Centers:

3.200 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Removable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

#### **Connector Locking Method:**

Latch

#### **Operating Tempurature Rating:**

Between 0.0 degrees celsius and 52.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## **Insert Material:**

Plastic polyester glass filled single mating end

# **Terminal Type:**

Crimp single mating end single contact grouping

# Included Contact Quantity:

50 single mating end single contact grouping

# Included Contact Type:

Flat pin single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold



## **Precious Material And Weight:**

0.050 gold grains, troy

## **Precious Material:**

Gold

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0