NSN 5935-01-342-0345



Electrical Receptacle Connector Body - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-342-0345 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.486 inches and 1.551 inches **Overall Height:** Between 1.335 inches and 1.351 inches **Overall Width:** Between 1.335 inches and 1.351 inches **Environmental Protection:** Moisture resistant and moisture proof and salt water resistant and shock proof and vibration proof and fungus resistant and thermal shock resistant and vibration resistant and shock resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.126 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.057 inches and 1.067 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.057 inches and 1.067 inches **Distance From Mounting Shoulder To Front Face:** Between 0.894 inches and 0.906 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-09 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 98.0 Shell Type: Solid

Connector Locking Method:

Bayonet pin

Operating Tempurature Rating:

Between -65.0 degrees celsius and 150.0 degrees celsius

Thready Qty Per Inch (tpi):

28

Thread Size:

1.128 inches

NSN 5935-01-342-0345

Electrical Receptacle Connector Body - Page 2 of 2



Digatic single mating and	
Plastic single mating end	
Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Cadmium and chromate	
Shell Surface Treatment Specification:	
Qq-p-416, type 2, cl 3 federal specification all treatment responses	
Test Data Document:	
81349-mil-c-81511 specification (includes engineering type bulletins, brod	chures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar tr	rade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are	shown as "typical", "average", "", etc.).
Thread Series Designator:	
Un	
Specification Data:	
81349-mil-c-81511/21 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	