NSN 5935-01-342-3370

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-342-3370

Body Style: Straight shape Overall Length: 3.917 inches Overall Height: 0.751 inches Overall Width: 0.244 inches Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Overall Length: 3.917 inches Overall Height: 0.751 inches Overall Width: 0.244 inches Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
3.917 inches Overall Height: 0.751 inches Overall Width: 0.244 inches Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Overall Height: 0.751 inches Overall Width: 0.244 inches Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Overall Width: 0.244 inches Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Overall Width: 0.244 inches Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
0.244 inches Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Mating End Quantity: 1 Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Contact Position Arrangement Style: 2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
2 rows of contacts non-inserted board single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
3.0 single mating end single contact grouping Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Connector Locking Method: Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Friction Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Terminal Location: Back single mating end single contact grouping Contact Material:
Back single mating end single contact grouping Contact Material:
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Printed circuit single mating end single contact grouping
Included Contact Quantity:
65 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.065 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a

NSN 5935-01-342-3370

Electrical Receptacle Connector - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A039b0