# NSN 5935-01-342-4509

Thread Class: 2a and 2b

**Thread Direction:** 

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-342-4509

Right-hand
Body Style:
Straight shape
Overall Length:
3.850 inches
Overall Height:
0.685 inches
Overall Width:
0.250 inches
Environmental Protection:
Vibration resistant and salt water resistant and corrosion resistant and humidity resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end

# NSN 5935-01-342-4509

Electrical Plug Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class i military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

### **Included Contact Quantity:**

70 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.070 gold grains, troy

#### **Precious Material:**

Gold

### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

# **Unit Of Measure:**

## **Demilitarization:**

No

# Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.