# NSN 5935-01-342-6660

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-342-6660 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 5.315 inches **Overall Height:** Between 0.520 inches and 0.610 inches **Overall Width:** 0.670 inches **Environmental Protection:** Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant **Distance Between Mounting Facility Centers:** 5.150 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 1.7 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -55.0 degrees celsius and 105.0 degrees celsius **Features Provided:** Pre-tinned terminal Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches

Terminal Location:

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

# NSN 5935-01-342-6660

Electrical Receptacle Connector - Page 2 of 2



### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic polyamide single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 1 federal specification 2nd treatment response single mating end single contact grouping

# **Terminal Type:**

Wire lead single mating end single contact grouping

### **Contact Material Specification:**

Qq-b-613 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

### **Shell Material:**

Aluminum alloy 6061

#### **Shell Surface Treatment:**

Anodize

### **Shell Surface Treatment Specification:**

Mil-a-8625, type ii military specification single treatment response

# **Shell Material Specification:**

Qq-a-200/8, t6 federal specification single material response

# **Insert Material Specification:**

Astm d4066-82, group i, class 2, grade i assn standard single material response single mating end

# **Included Contact Quantity:**

276 single mating end single contact grouping

### **Included Contact Type:**

Flat pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.276 gold grains, troy

### **Precious Material:**

Gold

# **Thread Series Designator:**

Unc

# Shelf Life:

N/a

### **Unit Of Measure:**

# **Demilitarization:**

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.