

View Online at <https://aerobasegroup.com/nsn/5935-01-342-6660>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

5.315 inches

**Overall Height:**

Between 0.520 inches and 0.610 inches

**Overall Width:**

0.670 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

5.150 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.7 single mating end single contact grouping

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Features Provided:**

Pre-tinned terminal

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 1 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Wire lead single mating end single contact grouping

**Contact Material Specification:**

Qq-b-613 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

**Shell Material:**

Aluminum alloy 6061

**Shell Surface Treatment:**

Anodize

**Shell Surface Treatment Specification:**

Mil-a-8625, type ii military specification single treatment response

**Shell Material Specification:**

Qq-a-200/8, t6 federal specification single material response

**Insert Material Specification:**

Astm d4066-82, group i, class 2, grade i assn standard single material response single mating end

**Included Contact Quantity:**

276 single mating end single contact grouping

**Included Contact Type:**

Flat pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.276 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.