Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-343-3603

| Thread Class: |
|---|
| 2a |
| Za Thread Direction: |
| |
| Right-hand |
| Body Style: |
| Straight shape, external coupling w/backshell |
| Unable To Decode: Unable to decode and unable to decode |
| |
| Overall Length: 2.328 inches |
| |
| Overall Height: |
| 1.750 inches |
| Overall Width: |
| 1.750 inches |
| Environmental Protection: |
| Corrosion resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.172 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.375 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.375 inches |
| Cable Entrance Diameter: |
| 1.094 inches |
| Distance From Mounting Shoulder To Front Face: |
| 1.000 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 12-323 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 16.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 700.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |

Electrical Receptacle Connector - Page 2 of 3



Insert Position In Deg: 288.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Compression nut Thready Qty Per Inch (tpi): 8 **Thread Size:** 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 17 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Furnished items - protective cover and chain **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.017 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Special acme Shelf Life: N/a Unit Of Measure:

Electrical Receptacle Connector - Page 3 of 3



Demilitarization:

No

Fiig:

A039b0