NSN 5935-01-343-8357

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-343-8357

Body Style:

Straight type

Overall Length:

Between 2.714 inches and 2.744 inches

Overall Height:

0.790 inches

Overall Width:

Between 0.479 inches and 0.509 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.086 inches and 0.092 inches

Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

13w6 single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -65.0 degrees celsius and 150.0 degrees celsius

Features Provided:

Pre-tinned terminal

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and copper single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end 1st contact grouping and mil-c-14550 military specification 2nd treatment response single mating end 1st contact grouping

NSN 5935-01-343-8357

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Printed circuit single mating end 1st contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type ii, class 2 federal specification all treatment responses
Shell Material Specification:
Astm-a-620 assn standard single material response
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
7 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.