

View Online at <https://aerobasegroup.com/nsn/5935-01-344-3887>

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

Between 99.2 millimeters and 99.8 millimeters

**Overall Height:**

28.2 millimeters

**Overall Width:**

6.4 millimeters

**Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

**Distance Between Mounting Facility Centers:**

Between 91.2 millimeters and 91.6 millimeters

**Threaded Device Type:**

Mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

1.6 millimeters

**Thread Pitch In Millimeters:**

0.35

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping or gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping or mil-g-45204, type 2, cl 1, grade c military specification 3rd treatment response single mating end single contact grouping and mil-c-14550, cl 4 military specification 4th treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

Key shape pin left-hand at 3 o'clock and key shape pin right-hand at 3 o'clock

**Insert Material Specification:**

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or gst-40f military specification 2nd material response single mating end

**Thread Tolerance Class:**

6h external

**Included Contact Quantity:**

65 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.062 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-dod-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Iso s

**Specification Data:**

81349-dod-c-55302/162 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-std-15504