NSN 5935-01-344-4910

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-344-4910 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 1.032 inches **Mounting Bushing Length:** 0.562 inches **Body Length:** 0.749 inches **Overall Diameter:** 0.375 inches **Bushing Accommodation Hole Shape:** Round w/double flat **Maximum Voltage Rating In Volts:** 8000.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Length:** 0.209 inches **Bushing Thru-hole Accommodation Width:** 0.255 inches **Capacitance In Picofarads:** 3.8 **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32

Thread Size: 0.250 inches

NSN 5935-01-344-4910

Tip Jack - Page 2 of 2



Terminal Type:
Tab, solder lug
Material:
Plastic, polyamide bodyplastic, polyamide bushingplastic, polyamide capphosphor bronze contactplastic, polyamide insulatorphosphor
bronze terminal
Material:
Plastic polyamide insulator
Surface Treatment:
Tin terminal
Surface Treatment:
Tin contacttin terminal
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03400