

View Online at <https://aerobasegroup.com/nsn/5935-01-344-8288>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Angle shape, pcb type

**Overall Length:**

1.185 inches

**Overall Width:**

0.419 inches

**Environmental Protection:**

Heat resistant and cold resistant

**Distance Between Mounting Facility Centers:**

Between 0.960 inches and 0.970 inches

**Threaded Device Type:**

Coupling facility and mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Shell Type:**

Solid

**Connector Locking Method:**

Post jacksocket

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 135.0 degrees celsius

**Thready Qty Per Inch (tpi):**

56 and 56

**Thread Size:**

0.086 inches and 0.086 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Printed circuit single mating end single contact grouping

**Shell Material:**

Aluminum alloy 380.0

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shell Material Specification:**

Qq-a-591 federal specification single material response

**Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

25 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Jackscrew type-female and location-left hand and jackscrew type-female and location-right hand

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.025 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.