

View Online at <https://aerobasegroup.com/nsn/5935-01-344-8969>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.248 inches

Overall Diameter:

Between 1.484 inches and 1.516 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

Between 0.910 inches and 0.920 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Threaded Device Type:

Back shell and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

13-8 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.219 inches

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Features Provided:

Scoopproof design

Thready Qty Per Inch (tpi):

24 and 20

Thread Size:

0.688 inches and 1.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, cl 3 or 4, grade b military specification single treatment response

Included Contact Quantity:

8 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Furnished items - spare contact

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.008 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef and unef

Specification Data:

96906-ms27468 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

N/A

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.