

View Online at <https://aerobasegroup.com/nsn/5935-01-344-8973>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Rectangular shape

**Overall Length:**

2.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.000 inches

**Overall Height:**

0.797 inches

**Overall Width:**

0.750 inches

**Unthreaded Mounting Hole Diameter:**

0.112 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.468 inches

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

42 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew

**Thready Qty Per Inch (tpi):**

40 and 40

**Thread Size:**

0.112 inches and 0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate mineral filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

42 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Jackscrew type-male and location-left hand and jackscrew type-male and location-right hand

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.042 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.