Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-345-2954

Body Style:

Straight shape

Overall Length:

Between 2.620 inches and 2.650 inches

Overall Height:

0.663 inches

Overall Width:

Between 0.590 inches and 0.620 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Distance Between Mounting Facility Centers:

Between 2.401 inches and 2.411 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

24w7 single mating end

Contact Removability:

Removable single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end 1st contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, cl 2

federal specification 2nd treatment response single mating end 1st contact grouping

Terminal Type:

Crimp single mating end 1st contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shell Material:	
Metal	
Shell Surface Treatment:	
Cadmium and chromate	
Shell Surface Treatment Sp	ecification:
Qq-p-416, type 2, cl 2 federa	I specification all treatment responses
Insert Material Specification	1:
Mil-m-14, ty sdg-f military spe	cification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification
2nd material response single	mating end
Included Contact Quantity:	
17 single mating end 1st cont	act grouping
Included Contact Type:	
Round socket single mating e	and 1st contact grouping
Precious Material And Loca	ition:
Contact surfaces gold	
Precious Material And Weig	jht:
0.017 gold grains, troy	
Precious Material:	
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	