Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-345-2956

## **Body Style:**

Straight shape

## **Overall Length:**

Between 2.714 inches and 2.744 inches

## **Overall Height:**

0.603 inches

## **Overall Width:**

Between 0.479 inches and 0.509 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant and shock resistant and salt water resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

#### Mating End Quantity:

1 Contact Position Arrangement Style:

# 37 single mating end

or single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Mating end

#### Shell Type:

Solid

## **Connector Locking Method:**

Friction

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 120.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## **Insert Material:**

Plastic polyamide single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2 or 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal

specification 2nd treatment response single mating end single contact grouping

## **Terminal Type:**

Pin single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Shell Material:

Steel

Shell Surface Treatment:

Chromate and cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses

## Included Contact Quantity:

37 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

## Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.037 gold grains, troy

## **Precious Material:**

Gold

Shelf Life:

N/a

## Unit Of Measure:

Demilitarization:

No

---

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.