## NSN 5935-01-345-3786

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-345-3786 **Body Style:** Straight shape, external coupling Overall Length: 0.330 inches **Overall Height:** 0.910 inches **Overall Width:** 0.562 inches **Unthreaded Mounting Hole Diameter:** 0.136 inches **Distance Between Mounting Facility Centers:** 0.587 inches **Distance From Mounting Shoulder To Front Face:** Between 0.253 inches and 0.283 inches **Mating End Quantity: Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 and 120.0 and 240.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Shell Material:** Copper alloy **Shell Surface Treatment:** Gold and nickel **Shell Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response and mil-c-26074 military specification 2nd treatment response **Shell Material Specification:** Qq-b-626, comp 22, half hard federal specification single material response **Precious Material And Location:** Shell surface gold **Precious Material And Weight:** 0.100 gold grains, troy **Precious Material:** Gold Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5935-01-345-3786

Receptacle Dummy Connector - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.