

View Online at https://aerobasegroup.com/nsn/5935-01-345-3793

Body Style:

Rectangular shape w/cable clamp

Overall Length:

Between 2.610 inches and 2.630 inches

Overall Height:

1.680 inches

Overall Width:

0.290 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

Cable Entrance Diameter:

1.590 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

40 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Hood, top opening

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1

federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Guide Design And Location:

D shape pin left-hand at 5 oclock v groove pin right-hand at 7: 30 oclock

Shell Material:

Aluminum alloy

NSN 5935-01-345-3793

Electrical Modular Plug Connector - Page 2 of 2



Shell Surface Treatment: Anodize Shell Surface Treatment Specification: Mil-a-8625 military specification single treatment response **Insert Material Specification:** Mil-m-14, ty sdg-f military specification single material response single mating end **Included Contact Quantity:** 40 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Cable clamp on back **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.040 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.
