

View Online at <https://aerobasegroup.com/nsn/5935-01-345-4989>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.230 inches

Environmental Protection:

Vibration resistant and shock resistant and thermal shock resistant and moisture resistant and pressure proof

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma 1st mating end nonstd 2nd mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

335.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

18.0 gigahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Width Across Flats:

0.688 inches

Operating Temperature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Thread Qty Per Inch (tpi):

36 and 28 and 28

Thread Size:

0.250 inches and 0.438 inches and 0.500 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 2 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550, class 4 military specification 2nd treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response all mating ends single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35, type 1 federal specification single treatment response

Shell Material Specification:

Ams-5640, type 303, condition a assn standard single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends or I-p-403, type 1 federal specification single material response all mating ends

Included Contact Quantity:

1 1st mating end single contact grouping 1 2nd mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.