

View Online at <https://aerobasegroup.com/nsn/5935-01-345-6102>

**Body Style:**

Rectangular shape w/cable clamp

**Overall Length:**

Between 2.610 inches and 2.630 inches

**Overall Height:**

1.680 inches

**Overall Width:**

0.290 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

**Cable Entrance Diameter:**

1.590 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

40 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Shell Type:**

Hood, top opening

**Connector Locking Method:**

Friction

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Guide Design And Location:**

V groove pin right-hand at 3 o'clock d shape pin left-hand at 12 o'clock

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Anodize

**Shell Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:**

40 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Cable clamp on back

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.040 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.