

View Online at <https://aerobasegroup.com/nsn/5935-01-346-3019>

**Body Style:**

Round flange mount

**Mounting Hole Circle Radius:**

2.188 inches

**Overall Diameter:**

3.625 inches

**Environmental Protection:**

Salt water resistant and vibration resistant and shock resistant

**Unthreaded Mounting Hole Diameter:**

0.190 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

4 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

40.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

450.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.020 silver grains, troy

**Precious Material:**

Silver

**Test Data Document:**

81349-mil-r-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-r-2726/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0