

View Online at https://aerobasegroup.com/nsn/5935-01-346-3354

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Hood, side opening w/clamp
Overall Length:
2.182 inches
Overall Height:
2.467 inches
Overall Width:
Between 0.428 inches and 0.448 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Cable Entrance Diameter:
0.220 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Polarization Method:
Shell and jackscrew
Shell Type:
Hood, side opening
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate



## Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 1 or 2 federal specification all treatment responses

## Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response or mil-p-19833, ty gdi-30f military specification single material response single mating end

Shell Guide Type And Location Designator:

A slot

## Test Data Document:

81349-mil-dtl-28748/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator:

Unc

Specification Data: 81349-mil-dtl-28748/4 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.