NSN 5935-01-346-3356

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-346-3356 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 2.578 inches **Overall Height:** 0.970 inches **Overall Width:** 1.016 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.123 inches and 0.128 inches **Distance Between Mounting Facility Centers:** Between 2.261 inches and 2.271 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20 20-20 single mating end **Polarization Method:** Shell and jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Insert Material:** Plastic diallyl phthalate glass filled single mating end **Shell Material:**

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

NSN 5935-01-346-3356

Electrical Receptacle Connector Body - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 1 or 2 federal specification all treatment responses

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single material response single mating end

Shell Guide Type And Location Designator:

F pin

Unable To Decode:

Unable to decode and unable to decode

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28748/3 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.