Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-346-4105

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.750 inches
Overall Diameter:
Between 2.296 inches and 2.328 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant
and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant
Distance From Mounting Shoulder To Front Face:
Between 1.691 inches and 1.701 inches
Mounting Facility Thickness:
Between 0.125 inches and 0.750 inches
Threaded Device Type:
Back shell and mounting bushing
Mating End Quantity:
1
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
300.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Operating Tempurature Rating:
Between -65.0 degrees celsius and 175.0 degrees celsius
Features Provided:
Pre-tinned terminal
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.438 inches and 1.750 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings



# **Contact Surface Treatment:**

Gold single mating end all contact groupings

#### **Insert Material:**

Plastic epoxy single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings

#### **Terminal Type:**

Crimp single mating end all contact groupings

#### **Shell Material:**

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

#### **Included Contact Quantity:**

2 single mating end 1st contact grouping97 single mating end 2nd contact grouping

# **Bushing Accommodation Hole Shape:**

Round w/flat

# Included Contact Type:

Triaxial socket single mating end 1st contact groupinground socket single mating end 2nd contact grouping

#### Special Features:

Furnished items - spare contact

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.107 gold grains, troy

# Precious Material:

Gold

# Thread Series Designator:

Unef and uns

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.