

View Online at <https://aerobasegroup.com/nsn/5935-01-346-4107>

**Body Style:**

Straight type

**Overall Length:**

2.500 inches

**Overall Height:**

0.960 inches

**Overall Width:**

0.350 inches

**Environmental Protection:**

Vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Distance Between Mounting Facility Centers:**

2.250 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyphenylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-b-626 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification 1st material response single mating end

**Included Contact Quantity:**

50 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.050 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.