

View Online at <https://aerobasegroup.com/nsn/5935-01-346-4121>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

0.844 inches

Overall Height:

1.797 inches

Overall Width:

3.578 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.123 inches and 0.128 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.761 inches and 0.771 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 3.417 inches and 3.427 inches

Distance From Mounting Shoulder To Front Face:

Between 0.620 inches and 0.735 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

75 single mating end

Polarization Method:

Jackscrew and shell

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625, type 1 or type 2 military specification single treatment response

Shell Material Specification:

Qq-a-250/8, temper 0 federal specification single material response or qq-a-250/1, temper h12 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, tygdi-30f military specification single material response single mating end

Shell Guide Type And Location Designator:

A pin

Unable To Decode:

Unable to decode and unable to decode

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28748/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.