NSN 5935-01-346-4977

Electrical Plug Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-346-4977 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Hood, side opening w/clamp **Overall Length:** 2.182 inches **Overall Height:** 2.619 inches **Overall Width:** Between 0.484 inches and 0.516 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Cable Entrance Diameter:** 0.220 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20 20-20 single mating end **Polarization Method:** Jackscrew and shell Shell Type: Hood, side opening **Connector Locking Method:** Jackscrew-socket **Connector Cable Strain Relief Method:** Cable clamp Thread Length: 0.320 inches **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Insert Material:**

Shell Material:

Plastic diallyl phthalate glass filled single mating end

Aluminum alloy

NSN 5935-01-346-4977

Electrical Plug Connector Body - Page 2 of 2



Shell Surface Treatment:
Anodize
Shell Surface Treatment S

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Shell Material Specification:

Qq-a-250/8 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response or mil-p-19833, type gdi-30f military specification single material response single mating end

Shell Guide Type And Location Designator:

B slot

Test Data Document:

81349-mil-dtl-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-dtl-28748/4 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.