

View Online at <https://aerobasegroup.com/nsn/5935-01-346-8641>

**Thread Class:**

2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

31.5 millimeters

**Overall Height:**

Between 33.0 millimeters and 33.6 millimeters

**Overall Width:**

Between 33.0 millimeters and 33.6 millimeters

**Unable To Decode:**

Unable to decode and unable to decode

**Unable To Decode:**

Unable to decode and unable to decode

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

24.61 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

24.61 millimeters

**Distance From Mounting Shoulder To Front Face:**

Between 19.5 millimeters and 20.9 millimeters

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

17-8 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0 and 67.0 and 164.0 and 218.0 and 280.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

**Thready Qty Per Inch (tpi):**

10

**Thread Size:**

25.0 millimeters and 1.188 inches

**Thread Pitch In Millimeters:**

1.00

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic epoxy single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Qq-n-290, cl2 federal specification single treatment response

**Thread Tolerance Class:**

6g external

**Included Contact Quantity:**

8 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.008 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Iso m and special acme

**Specification Data:**

81349-mil-c-38999/20 government specification

**Shelf Life:**

Nil

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.