NSN 5935-01-346-9629

Aluminum alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-346-9629

Body Style:
Straight shape, flush mount
Overall Length:
0.891 inches
Overall Height:
4.354 inches
Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
4.026 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.436 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
"106, a106" single mating end
Contact Removability:
Removable single mating end all contact groupings
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c, class 1 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:

NSN 5935-01-346-9629

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and nickel
Included Contact Quantity:
106 single mating end 1st contact grouping106 single mating end 2nd contact grouping106 single mating end 3rd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.318 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
4039h0