

View Online at <https://aerobasegroup.com/nsn/5935-01-347-1570>

Body Style:

Straight shape, external coupling

Overall Length:

34.1 millimeters

Overall Height:

Between 45.5 millimeters and 46.6 millimeters

Overall Width:

Between 45.5 millimeters and 46.6 millimeters

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 3.6 millimeters and 4.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

38.1 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

38.1 millimeters

Distance From Mounting Shoulder To Front Face:

Between 19.2 millimeters and 20.8 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

25-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

0.0 and 70.0 and 290.0

Shell Type:

Solid

Connector Locking Method:

Detent

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Features Provided:

Scoopproof design

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, cl 3 or 4, grade b military specification single treatment response

Included Contact Quantity:

128 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.128 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-dod-c-38999/42 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.