NSN 5935-01-347-2062

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-347-2062 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Black **Body Style:** Threaded bushing mounted **Overall Length:** 1.100 inches **Mounting Bushing Length:** 0.540 inches **Body Length:** 0.870 inches **Overall Diameter:** 0.600 inches **Bushing Accommodation Hole Shape:** Round w/double flat **Maximum Voltage Rating In Volts:** 1200.0 ac and 1200.0 dc **Accommodated Finger Type:** Banana spring single finger **Finger Accommodation Diameter:** 0.166 inches single finger **Finger Accommodation Length:** 0.750 inches single finger **Bushing Thru-hole Accommodation Length:** 0.450 inches **Bushing Thru-hole Accommodation Width:** 0.500 inches **End Application:** Support equipment (se), b-2 bomber, low altitute navigation & targeting infrared system (lantirn), aircraft, eagle f-15, advanced cruise missile, acm-129 **Current Rating In Amps:** 15.0 **Mounting Facility Type And Quantity:** 1 bushing

Thread Size: 0.500 inches

28

Thready Qty Per Inch (tpi):

NSN 5935-01-347-2062

Tip Jack - Page 2 of 2



Criticality Code Justification:
Feat
Terminal Type:
Turret
Special Features:
Weapon system essential
Material:
Plastic, polycarbonate insulator
Material:
Plastic polycarbonate insulator
Surface Treatment:
Nickel terminal
Surface Treatment:
Nickel spring
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03400