

View Online at <https://aerobasegroup.com/nsn/5935-01-347-2062>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated completely

**Identification Code Color:**

Black

**Body Style:**

Threaded bushing mounted

**Overall Length:**

1.100 inches

**Mounting Bushing Length:**

0.540 inches

**Body Length:**

0.870 inches

**Overall Diameter:**

0.600 inches

**Bushing Accommodation Hole Shape:**

Round w/double flat

**Maximum Voltage Rating In Volts:**

1200.0 ac and 1200.0 dc

**Accommodated Finger Type:**

Banana spring single finger

**Finger Accommodation Diameter:**

0.166 inches single finger

**Finger Accommodation Length:**

0.750 inches single finger

**Bushing Thru-hole Accommodation Length:**

0.450 inches

**Bushing Thru-hole Accommodation Width:**

0.500 inches

**End Application:**

Support equipment (se), b-2 bomber, low altitute navigation & targeting infrared system (lantirn), aircraft, eagle f-15, advanced cruise missile, acm-129

**Current Rating In Amps:**

15.0

**Mounting Facility Type And Quantity:**

1 bushing

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.500 inches

Criticality Code Justification:

Feat

Terminal Type:

Turret

Special Features:

Weapon system essential

Material:

Plastic, polycarbonate insulator

Material:

Plastic polycarbonate insulator

Surface Treatment:

Nickel terminal

Surface Treatment:

Nickel spring

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400