

View Online at <https://aerobasegroup.com/nsn/5935-01-347-5832>

**Thread Class:**

2a and 2b and 2a

**Thread Direction:**

Right-hand and right-hand and right-hand

**Body Style:**

Straight shape, rectangular

**Overall Length:**

Between 2.261 inches and 2.271 inches

**Overall Height:**

0.970 inches

**Overall Width:**

1.016 inches

**Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant and corrosion resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.123 inches and 0.128 inches

**Distance Between Mounting Facility Centers:**

Between 2.261 inches and 2.271 inches

**Threaded Device Type:**

Coupling facility and back shell

**Mating End Quantity:**

15

**Contact Position Arrangement Style:**

20 20-20 single mating end

**Polarization Method:**

Jackscrew and shell

**Shell Type:**

Solid

**Connector Locking Method:**

Jackscrew-socket

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

32 and 32 and 40

**Thread Size:**

0.138 inches and 0.138 inches and 0.138 inches

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester single mating end

**Shell Material:**

Aluminum alloy or aluminum alloy 360.0

**Shell Surface Treatment:**

Cadmium and chromate or nickel

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 1 or 2 federal specification single treatment response

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single material response single mating end

**Shell Guide Type And Location Designator:**

Bn pin

**Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc and unc and unc

**Specification Data:**

81349-mil-c-28748/3 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-14 spec.