AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-347-6507

Thread Direction: Right-hand Seal Material: Rubber, silicone base Overall Longth: 3.560 inches Overall Height: 1.145 inches Overall Width: 1.150 inches Cable Opening Diameter: Between 0.250 inches and 0.437 inches Thread Longth: 7.11 millimeters Cable Opening Quantity: 1 7.11 millimeters Cable Opening Quantity: 1 7.11 millimeters Coronnet and preformed packing Size Designation: 7 7 Mounting Facility Type And Quantity: 1 threadd coupling Chread Pitch In Millimeters: 2.50 millimeters Thread Tolerance Class: 6 Internal Material: Aluminum aloy Surface Treatment: Cadmium and nickel Stright type wicable damp Surface Treatment: Cadmium and nickel, electroless Thread Selig Designator: Istright type wicable damp <	view Online at https://aerobasegroup.com/nsn/3933-01-347-0307	
Sel Material: Rubber, silicone base Overall Length: 3.560 Inches Overall Height: 1.145 inches Overall Witth: 1.150 inches Cable Opening Diameter: Between 0.250 inches and 0.437 inches Thread Length: 7.11 millineters Cable Opening Quantity: 1 Seal Type: Grommet and preformed packing Size Designation: 17 Monting Facility Type And Quantity: 1 Thread Size: 250 on Millimeters: 1.00 Thread Tolerance Class: 6 Intenal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Stright type wickable clamp Surface Treatment: Cadmium an nickel, electroless Thread Series Designator: Stright type wickable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Stright type wickable clamp	Thread Direction:	
Rubber, silicone base Overall Length: 3.560 inches Overall Width: 1.145 inches Overall Width: 1.145 inches Overall Width: 1.150 inches Cable Opening Diameter: Between 0.250 inches and 0.437 inches Thread Length: 7.11 millimeters Cable Opening Quantity: 1 Seal Type: Grommet and preformed packing Size Designation: 7 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters 1.00 Thread Tolerance Class: 1.100 Thread Tolerance Class: 1.01 Surface Treatment: Cadmium and nickel Style Designato: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Des	Right-hand	
Overall Length:3.560 inchesSoverall Height:1.145 inchesOverall Width:1.145 inchesOverall Width:1.150 inchesCable Opening Diameter:Between 0.250 inches and 0.437 inchesThread Length:7.11 millimetersCable Opening Quantity:1Seal Type:Grommet and preformed packingSize Designation:7Mounting Facility Type And Quantity:1 threaded couplingThread Size:25.0 millimeters1.00Thread Tolerance Class:Auminum alloySurface Treatment:Cadmium and nickelStright type w(cable clampSurface Treatment:Cadmium and nickel, electrolessThread SizeStright type w(cable clampSurface Treatment:Cadmium and nickel, electrolessThread Stright type Mode clampSurface Treatment:Cadmium and nickel, electrolessThread Stright type Mode clampSurface Treatment:Cadmium and nickel, electrolessStright type w(cable clamp <t< td=""><td>Seal Material:</td><td></td></t<>	Seal Material:	
3.560 inchesOverall Height:1.145 inchesOverall Width:1.150 inchesCable Opening Diameter:Between 0.250 inches and 0.437 inchesThread Length:7.11 millimetersCable Opening Quantity:1Seal Type:Grommet and preformed packingSize Designation:17Mounting Facility Type And Quantity:1 threadd couplingThread Jize:2.5.0 millimeters:1.00Thread Size:2.1.00Thread Tolerance Class:6h internalMaterial:Auminum alloySurface Treatment:Cadmium an nickelStriaght type wicable clampCatrain and nickel, electrolessThread FreetinestCadmium and nickel, electrolessThread FreetinestSurface Treatment:Cadmium and nickel, electrolessThread Steries Designator:Striaght type wicable clampSurface Treatment:Cadmium and nickel, electrolessThread Steries Designator:Iso mSheff Life:Na	Rubber, silicone base	
Overall Height:1.145 inchesOverall Width:1.150 inchesCable Opening Diameter:Between 0.250 inches and 0.437 inchesThread Length:7.11 millimetersCable Opening Quantity:11 millimetersCable Opening Quantity:1Seal Type:Grommet and preformed packingSize Designation:17Mounting Facility Type And Quantity:1 threaded couplingThread Size:25.0 millimeters100Thread Tolerance Class:6h internalMaterial:Auminum alloySurface Treatment:Cadmium an nickelStriaght type wicable clampCurface Treatment:Cadmium an nickel, electrolessThread Series Designator:Striaght type wicable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Striaght type wicable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Striaght type wicable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso mSheft Life:Nra	Overall Length:	
1.45 indes Overall Width: 1.150 inches Cable Opening Diameter: Between 0.250 inches and 0.437 inches Thread Length: 7.11 millimeters Cable Opening Quantity: 1 Seal Type: Grommet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters Thread Fitch In Millimeters: 1.00 Thread Tolerance Class: 6 internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Stringht type wicable clamp Surface Treatment: Cadmium and nickel, electroless Thread String Stringent The Stringent Th	3.560 inches	
Overall Width:1.150 inchesCable Opening Diameter:Between 0.250 inches and 0.437 inchesThread Length:7.11 millimetersCable Opening Quantity:1Seal Type:Grommet and preformed packingSize Designation:17Mounting Facility Type And Quantity:1 threaded couplingThread Size:25.0 millimeters1.00Thread Folderance Class:6 internalMaterial:Aluming numbers:1.00Strafe Treatment:Cadmium and nickelSurface Treatment:Cadmium and nickel, electrolessStrafes Treat Straine:Cadmium and nickel, electrolessThread Straine:Strafe Treatment:Cadmium and nickel, electrolessThread Straine:Strafe Treatment:Cadmium and nickel, electrolessThread Straine:Strafe Treatment:Cadmium and nickel, electrolessThread Straine:Strafe Treatment:Strafe Treatment:Strafe Treatm	Overall Height:	
1.150 inches Cable Opening Diameter: Between 0.250 inches and 0.437 inches Thread Length: 7.11 millimeters Cable Opening Quantity: 1 Seal Type: Grommet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters 1.00 Thread Tolerance Class: 61 internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Stringht type w/cable clamp Stringht type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Stries Designator: Stringht type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Stries Designator: Stringht type w/cable clamp Material: Na	1.145 inches	
Cable Opening Diameter: Between 0.250 inches and 0.437 inches Thread Length: 7.11 millimeters Cable Opening Quantity: 1 Seal Type: Grommet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters Thread Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Store Store Store <tr< td=""><td>Overall Width:</td><td></td></tr<>	Overall Width:	
Between 0.250 inches and 0.437 inches Thread Length: 7.11 millimeters Cable Opening Quantity: 1 Seal Type: Grommet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Atuminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Sheff Life: Na	1.150 inches	
Thread Length: 7.11 millimeters Cable Opening Quantity: 1 Seal Type: Grommet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters 1.00 Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6 hinternal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Cadmium and nickel, electroless Thread Series Designator: Strafes Treatment: Cadmium and nickel, electroless Thread Series Designator: Strafes Treatment: Cadmium and nickel, electroless Thread Series Designator: Strafes Treatment: Cadmium and nickel, electroless Thread Series Designator: Strafes Treatment: Cadmium and nickel, electroless Thread Series Designator: Strafes Treatment: Cadmium a	Cable Opening Diameter:	
7.11 millimeters Cable Opening Quantity: 1 Seal Type: Grommet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 1 threaded coupling Thread Size: 25.0 millimeters Thread Size: 25.0 millimeters 1.00 Thread Tolerance Class: 6 hinernal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shift Life: Na	Between 0.250 inches and 0.437 inches	
Cable Opening Quantity: 1 Seal Type: Grommet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 1 threaded coupling Thread Size: 25.0 millimeters 1.00 Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Stright type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shift Life: Na	Thread Length:	
1 Seal Type: Grommet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6 hinternal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Straight type w/cable clamp	7.11 millimeters	
Seal Type: Grommet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Stradget type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Stradget type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Sheff Life: N/a	Cable Opening Quantity:	
Gromet and preformed packing Size Designation: 17 Mounting Facility Type And Quantity: 1 threaded coupling Thread Goupling Thread Size: 25.0 millimeters 25.0 millimeters 25.0 millimeters 1.00 Thread Tolerance Class: 6 hinternal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Straight type w/cable clamp Straight type m/cable clamp S	1	
Size Designation:17Mounting Facility Type And Quantity:1 threaded couplingThread Size:25.0 millimeters25.0 millimetersThread Pitch In Millimeters:1.00Thread Tolerance Class:6 hinternalMaterial:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso mShelf Life:Na	Seal Type:	
17 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 25.0 millimeters 25.0 millimeters 25.0 millimeters 1.00 Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 1.00 Thread Tolerance Class: 6 hinternal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: Na	Grommet and preformed packing	
Mounting Facility Type And Quantity:1 threaded couplingThread Size:25.0 millimeters25.0 millimetersThread Pitch In Millimeters:1.00Thread Tolerance Class:6h internalMaterial:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso mShelf Life:N/a	Size Designation:	
1 threaded coupling Thread Size: 25.0 millimeters 25.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6 h internal 6 h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	17	
Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	Mounting Facility Type And Quantity:	
25.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Aufrace Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	1 threaded coupling	
Thread Pitch In Millimeters:1.00Thread Tolerance Class:6h internalMaterial:Material:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso mShelf Life:N/a	Thread Size:	
1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	25.0 millimeters	
Thread Tolerance Class:6h internalMaterial:Material:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso mShelf Life:N/a	Thread Pitch In Millimeters:	
6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	1.00	
Material:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso mShelf Life:N/a	Thread Tolerance Class:	
Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	6h internal	
Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	Material:	
Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	Aluminum alloy	
Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	Surface Treatment:	
Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	Cadmium and nickel	
Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	Style Designator:	
Cadmium and nickel, electroless Thread Series Designator: Iso m Shelf Life: N/a	Straight type w/cable clamp	
Thread Series Designator: Iso m Shelf Life: N/a	Surface Treatment:	
Iso m Shelf Life: N/a	Cadmium and nickel, electroless	
Shelf Life: N/a	Thread Series Designator:	
N/a	lso m	
	Shelf Life:	
Unit Of Measure:	N/a	
	Unit Of Measure:	

Electrical Connector Backshell - Page 2 of 2



Demilitarization:

No

Fiig:

A10100