## NSN 5935-01-347-7183

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-347-7183

**Body Style:** 

Straight shape

**Overall Length:** 

Between 6.745 inches and 6.755 inches

**Overall Height:** 

0.995 inches

Overall Width:

Between 0.575 inches and 0.585 inches

**Environmental Protection:** 

Vibration resistant and salt water resistant and shock resistant and humidity resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.115 inches and 0.125 inches

**Distance Between Mounting Facility Centers:** 

6.450 inches

**Mating End Quantity:** 

1

#### **Contact Position Arrangement Style:**

4 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:** 

Mating end

**Connector Locking Method:** 

Friction

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic polyphenylene single mating end and glass fiber single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Printed circuit single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

# NSN 5935-01-347-7183

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-p-46174, cl 40, grade e military specification all material responses single mating end

## **Included Contact Quantity:**

240 single mating end single contact grouping

## **Included Contact Type:**

Square socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.240 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.