Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-347-8827

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.310 inches
Overall Height:
0.860 inches
Overall Width:
0.380 inches
Environmental Protection:
Heat resistant and cold resistant
Distance Between Mounting Facility Centers:
1.000 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 150.0 degrees celsius
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

NSN 5935-01-347-8827

Electrical Receptacle Connector - Page 2 of 2



Plastic diallyl	phthalate glass filled single mating end
	ace Treatment Specification:
Mil-g-45204 n	nilitary specification single treatment response single mating end single contact grouping
Terminal Typ	e:
Crimp single r	nating end single contact grouping
Insert Materia	al Specification:
Mil-m-14, ty s	dg-f military specification single material response single mating end
Unable To De	ecode:
Unable to dec	ode and unable to decode
Included Cor	ntact Quantity:
9 single matin	g end single contact grouping
Included Cor	ntact Type:
Round socket	single mating end single contact grouping
Precious Mat	erial And Location:
Contact surfa	ces gold
Precious Mat	erial And Weight:
0.009 gold gra	ains, troy
Precious Mat	erial:
Gold	
Thread Serie	s Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Meas	ure:
Demilitarizati	ion:
No	
Fiig:	
A039b0	
Mil-std (milita	ary Standard):
Mil-g-45204 s	pec.