

View Online at <https://aerobasegroup.com/nsn/5935-01-347-9891>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/strain relief

Overall Length:

7.538 inches

Diameter:

Between 3.219 inches and 3.270 inches

Overall Diameter:

3.563 inches

Environmental Protection:

Thermal shock resistant and pressure proof and humidity resistant and moisture resistant and corrosion resistant and chemical resistant and dust resistant and shock resistant and vibration resistant

Cable Entrance Diameter:

Between 0.875 inches and 2.365 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

24-354 single mating end

Contact Removability:

Removable single mating end all contact groupings

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Cable clamp

Operating Temperature Rating:

Between -67.0 degrees celsius and 225.0 degrees celsius

Thready Qty Per Inch (tpi):

8

Thread Size:

0.125 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings

Insert Material:

Plastic phenolic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Chromate

Included Contact Quantity:

3 single mating end 1st contact grouping11 single mating end 2nd contact grouping61 single mating end 3rd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.087 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Double stub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.