## NSN 5935-01-348-4243

Steel

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-348-4243

Body Style:
Straight shape
Overall Length:
2.630 inches
Overall Height:
0.573 inches
Overall Width:
0.600 inches
Unthreaded Mounting Hole Diameter:
0.122 inches
Distance Between Mounting Facility Centers:
2.405 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -67.0 degrees celsius and 150.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Printed circuit single mating end single contact grouping
Shell Material:

## NSN 5935-01-348-4243

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Chromate and zinc
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.