Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-348-4246

Thread Class:
Thread Direction:
Right-hand
Body Style:
Straight type
Overall Length:
6.050 inches
Overall Height:
0.625 inches
Overall Width:
Environmental Protection:
Humidity resistant and fuel resistant and vibration resistant and shock resistant
Distance Between Mounting Facility Centers:
5.700 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
Contact Position Arrangement Style:
4 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290
federal specification 2nd treatment response single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:	
Pin single mating	end single contact grouping
Contact Material	Specification:
Qq-b-626, compos	sition 360 federal specification single material response single mating end single contact grouping
Insert Material Sp	pecification:
Mil-m-14, type sdg	f military specification single material response single mating end
Included Contact	Quantity:
204 single mating	end single contact grouping
Included Contact	: Туре:
Round socket sing	le mating end single contact grouping
Precious Materia	I And Location:
Contact surfaces	gold
Precious Materia	I And Weight:
0.204 gold grains,	troy
Precious Materia	I:
Gold	
Thread Series De	esignator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military S	Standard):
Mil-g-45204 spec.	