

View Online at <https://aerobasegroup.com/nsn/5935-01-349-0057>

Body Style:

Rectangular shape, angle

Overall Length:

1.562 inches

Overall Height:

0.625 inches

Overall Width:

0.875 inches

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

1.312 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

15 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

28.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

End Application:

Landing craft air cushion (lcac); seawolf class ssn; sprunace class dd (963); arleigh burke class ddg; austin ship class lpd-4 amphibious transport docks; forestal class cv; oliver perry class ffg; nimitz class cvn; los angeles class ssn (688); ticonderoga class cg (47)

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end single contact grouping

Shell Material:

Metal

Included Contact Quantity:

15 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.015 gold grains, troy

Precious Material:

Gold

Specification Data:

28480-1252-2401 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0