## NSN 5935-01-349-0057

**Terminal Type:** 

Pin single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-349-0057

Body Style:
Rectangular shape, angle
Overall Length:
1.562 inches
Overall Height:
0.625 inches
Overall Width:
0.875 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
1.312 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
15 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
28.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
End Application:
Landing craft air cushion (lcac); seawolf class ssn; sprunace class dd (963); arleigh burke class ddg; austin ship class lpd-4 amphibious
transport docks; forestal class cv; oliver perry class ffg; nimitz class cvn; los angeles class ssn (688); ticonderoga class cg (47)
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Criticality Code Justification:
Feat

## NSN 5935-01-349-0057

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Metal
Included Contact Quantity:
15 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Weapon system essential
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.015 gold grains, troy
Precious Material:
Gold
Specification Data:
28480-1252-2401 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0