## NSN 5935-01-349-0069

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-349-0069

Body Style:
Rectangular shape
Overall Length:
2.175 inches
Overall Height:
0.700 inches
Overall Width:
0.610 inches
Environmental Protection:
Corrosion resistant and humidity resistant
Unthreaded Mounting Hole Diameter:
0.103 inches
Distance Between Mounting Facility Centers:
Between 1.837 inches and 1.847 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290
federal specification 2nd treatment response single mating end single contact grouping
Terminal Type:

\_ . . . . . . .

Solder well single mating end single contact grouping

**Contact Material Specification:** 

Astm-b-103 assn standard single material response single mating end single contact grouping

## NSN 5935-01-349-0069

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel or plastic
Insert Material Specification:
Mil-m-14, ty mdg military specification single material response single mating end
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.024 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83515 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-83515/2 government specification
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):