NSN 5935-01-349-1852

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-349-1852 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** Between 1.776 inches and 1.806 inches **Overall Height:** 1.150 inches **Overall Width:** 2.275 inches **Environmental Protection:** Corrosion resistant and vibration resistant and shock resistant and humidity resistant **Unthreaded Mounting Hole Diameter:** 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.997 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.900 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 52 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Polarization boss Shell Type: **Connector Locking Method:** Jackscrew-socket **Operating Tempurature Rating:** Between -65.0 degrees celsius and 150.0 degrees celsius **Thread Size:**

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-349-1852

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Contact Surface Treatment Specification:
Mil-g-45402, type 2, grade b or c military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel comp 303
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Shell Material Specification:
Qq-s-764 federal specification single material response
Insert Material Specification:
Mil-m-14f, ty sdg-f military specification single material response single mating end
Included Contact Quantity:
52 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.052 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45402 spec.