NSN 5935-01-349-1854

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-349-1854

Body Style:
Angle shape
Overall Length:
1.960 inches
Overall Height:
1.332 inches
Overall Width:
0.422 inches
Body Length:
1.460 inches
Body Height:
0.722 inches
Environmental Protection:
Corrosion resistant and fungus resistant and humidity resistant and shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.093 inches and 0.105 inches
Distance Between Mounting Facility Centers:
1.060 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
300.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 120.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

Insert Material:

Plastic polyester glass filled single mating end

NSN 5935-01-349-1854

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Astm-b-122 assn standard single material response single mating end single contact grouping or cda260 assn standard single material response single mating end single contact grouping or ca-725 assn standard single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, type gpt-15f, gpt-20f or gpt-30f military specification single material response single mating end

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Square pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83503 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-83503/24 government specification

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.