## NSN 5935-01-349-5449

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-349-5449 **Body Style:** Straight shape **Overall Height:** 0.750 inches **Overall Width:** 0.300 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 2.5 single mating end single contact grouping **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -40.0 degrees celsius and 105.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Printed circuit single mating end single contact grouping **Included Contact Quantity:** 14 single mating end single contact grouping **Included Contact Type:** Square pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.014 gold grains, troy **Precious Material:** Gold Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5935-01-349-5449

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.